



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon-produktion.de
http: //www.chamaeleon-produktion.de

ТЕХНИЧЕСКИ ЛИСТ

СТРУКТУРА НА СПРЕЙ

Код

26340

Техническа информация:

Структура на Спрей текстура- възстановява структурата на повредени пластмаси или външни части на автомобила напр. брони, огледала, каси на врати и тунинг части, както и интериора на автомобила напр. табло, облицовка на вратата, централна конзола и облицовка на багажника.

Употреба:

Идеален за частична поправка и покритие на всички пластмасови части на автомобила.

Качества:

- Възпроизвежда структурата на повредени пластмаси и пластмасови части
- Черен цвят
- Лесно, спестяващо време приложение
- Подходящ за външни пластмасови части за автомобили, напр. вратирамки, огледала, тунинг части и брони, както и интериори напр. табло, централна конзола, панели на вратите и облицовка на багажника

Физични и химични свойства:

- Основа на свързващото вещество: Винилкополимер
- Цвят: черен
- Мирис: разтворител
- Степен на гланц: (при ъгъл на измерване 60 ° съгл. DIN 67530) гланц: > 15 гланцови единици

Ефективност:

- В зависимост от консистенцията и цвета: 400 ml са достатъчни за 1,0 - 1,5 м²
- **Основа:**
 - Повредени зони на всички пластмасови части отвятре и отвън, които ще се боядисват след структурата на спрей. Време за изсъхване (при 20 ° C, 50% относителна влажност на въздуха):
 - Сух на прах: след припл. 10 минути Суха на допир: след припл. 30 минути Времето за сушене зависи от околната температура, влажността на въздуха и дебелината на нанесения слой. Температурна устойчивост: до 80 ° C
- **Устойчивост при съхранение**

- 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- Size:**
- Aerosol cans, maximum nominal volume 400 ml
- VOC-value:** 244,1g
- **Aerosol Coating Category:** Automotive Bumper and Trim Product
 - **PW/MIR:** 0,71

Environment and labelling:

Environmentally compatible: Chamäleon is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of Chamäleon comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the Globally Harmonized System of Classification and Labelling of Chemicals(GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions:


Before use, carefully read and observe the warning texts on the label!

Application

- Clean surface thoroughly with Chamäleon Silicone Remover.
- Damaged area must be dry and free of dust and grease
- Shake can vigorously for 2 minutes
- Carry out spray test
- The structural density and effect is dependent on the numer of coats and the spraying distance
- Apply several thin coats to get desired texture
- Recoat once it has dried for approx. 15-20 min (20°C)
- Must be recoated

For professional use only

Wear an appropriate respirator (recommended type A2/P3)



Hints concerning application:


If you are using Structure Spray (black) it will be easy to smooth out any unevenness since it can be very easily sanded after drying. Structure adjustments can also be carried out in a simple manner. For instance: the surface has become too rough because the application was too thick. After drying and sanding, you can thinly apply the black structure spray once more. Our recommendation: Use a piece of cardboard to test the spraying process before the actual application by spraying at different distances.




2 min




depends on
effect



20°C=15-20
min



2-3 min



Data: 16, January 2018

This release replaces all eventually earlier issued versions.

For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de

See information on safety in Safety Data Sheet.